

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the Application:

1. (Currently Amended) A method of operating an end node in a communications system including at least one network node and said end node, the method comprising:
 - generating at the end node, from Mobile IP signals directed to said end node or transmitted by said end node, a list of network nodes identifying network nodes used in routing signals to or from said end node, said Mobile IP signals including at least one of a Mobile IP agent solicitation message, a Mobile IP agent advertisement message, a Mobile IP registration message and a Mobile IP registration reply message;
 - receiving [[,]] a fault signal indicating a network node fault;
 - determining, at the end node, using said generated list, if the network node fault corresponds to a network node that is used in routing signals to or from said end node;
 - and
 - if it is determined that the network node fault corresponds to a network node that is used in routing of signals to or from said end node, operating the end node to initiate a fault response operation.
2. (Currently Amended) The method of claim 1, wherein said determining if the network node fault corresponds to a network node that is used in routing signals to or from said end node comprises: ~~step includes:~~
 - comparing network node information included in the received fault signal to information in said generated list identifying at least one network node used in routing signals to or from said end node.
3. (Previously Presented) The method of claim 2, further comprising:
 - determining said fault response operation as a function of information stored in said end node, said stored information relating to a plurality of possible operations.

4. (Currently Amended) The method of claim 1, wherein said operating the end node to initiate a fault response operation comprises:

initiating said fault response operation as a function of fault response information stored in said end node, said stored fault response information relating to a plurality of possible operations; and

wherein said initiating said fault response operation is also performed as a function of the network node at which the fault occurred with said operation being elected from a plurality of possible operations based on both the type of fault and which one of a plurality of network nodes was the node at which the fault occurred.

5. (Currently Amended) The method of claim 3, wherein said stored information further comprises ~~identifying at least one network node used in routing signals to or from said end node~~ includes: a list of network nodes used in the routing of signals to said end node.

6. (Canceled)

7. (Currently Amended) The method of claim 5, wherein said stored information further comprises ~~includes~~ information identifying a network node which is used by said end node as an access node through which said end node is coupled to other nodes in the communications network.

8. (Original) The method of claim 7, wherein the access node is a base station and wherein said end node is a mobile device that is coupled to said base station by a wireless communications link.

9. (Currently Amended) The method of claim 4, further comprising ~~the step of:~~
dynamically generating at least a portion of said stored information identifying network nodes used in routing of signals to or from said end node from information included in sign is sent to or from said end node.

10. (Currently Amended) The method of claim 9, wherein said ~~step of~~ dynamically generating at least a portion of said stored information identifying network nodes comprises:
~~includes~~:

operating the end node to monitor for non-fault related signals and to generate at least some of said stored information from the monitored non-fault related signals.

11. (Original) The method of claim 10, wherein said non-fault related signals include session signaling messages communicated to or from said end node.

12. (Original) The method of Claim 10, wherein said non-fault related signals are routing messages.

13. (Currently Amended) The method of claim 1, wherein said fault response operation comprises ~~being~~ a Mobile IP registration operation.

14. (Currently Amended) The method of claim 1, wherein said fault response operation comprises ~~being~~ an end node state update operation.

15. (Canceled)

16. (Canceled)

17. (Canceled)

18. (Currently Amended) The method of claim 1, further comprising ~~the steps of~~:
receiving a fault signal at a first network node; and
sending a network node fault signal to said end node in response to receiving a fault signal.

19. (Currently Amended) The method of claim 18, wherein said ~~step of~~ sending a network node fault signal comprises ~~includes~~ periodically sending fault signals to a plurality of end nodes at preselected time intervals.

20. (Original) The method of claim 19, further comprising:

operating at least some of said plurality of end nodes to monitor for fault signals at said preselected time intervals but not between said preselected time intervals.

21. (Original) The method of claim 20, wherein said fault signals are messages, each message including at least one IP packet.

22. (Canceled)

23. (Canceled)

24. (Canceled)

25. (Currently Amended) The method of claim 1, wherein said fault response operation comprises accessing stored information, identifying a plurality of possible operations and selecting from the plurality of possible operations the operation to be performed based on both the type of fault and which one of a plurality of network nodes was the indicated network node at which the fault occurred.

26. (Canceled)

27. (Canceled)

28. (Canceled)

29. (Canceled)

30. (Currently Amended) The method of claim 25, wherein said stored information ~~comprises~~ includes information identifying a network node which is used by said end node as at least one of a Mobile IP home agent, a Session Initiation Protocol proxy server and a Session Initiation Protocol location registrar.

31. (Canceled)

32. (Canceled)

33. (Previously Presented) The method of claim 25, further comprising ~~the step of:~~ dynamically generating at least a portion of said stored information identifying network nodes used in routing signals to said end node from information included in signals sent to or from said end node.

34. (Canceled)

35. (Previously Presented) The method of claim 25, further comprising:
operating said end node to monitor for fault signals at preselected time intervals
but not between said preselected time intervals.

36. (Canceled)

37. (Canceled)

38. (Canceled)

39. (Currently Amended) A mobile communications device, comprising:
means for storing a set of information indicating network nodes which are used in
routing of signals either to said mobile communications device or from said mobile
communications device to other network nodes;
means for receiving messages from network nodes including service interference
notification messages indicating service interference at a network node;
means for generating at said mobile communications device, from Mobile IP
signals directed to said mobile communications device or transmitted by said mobile
communications device, a list of network nodes identifying network nodes used in routing
signals to or from said mobile communications device, said Mobile IP signals including
at least one of a Mobile IP agent solicitation message, a Mobile IP agent advertisement
message, a Mobile IP registration message and a Mobile IP registration reply message;
means for processing received service interference notification messages, at said
mobile communications device to determine, using said generated list, if service
interference indicated by a received network service interference notification message
indicates service interference at a network node used in routing of signals either to said
mobile communications device or from said mobile communications device to another
network node; and
means for initiating a fault response operation.

40. (Currently Amended) The mobile communications device of claim 39, further comprising: wherein said device includes

a wireless transmitter means for wireless transmission; and

wherein said means for receiving messages comprises ~~includes~~ a radio receiver circuit.

41. (Previously Presented) The mobile communications device of claim 40, further comprising:

means for controlling the mobile communications device to monitor for said service interference notification messages at preselected intervals but not between said preselected time intervals.

42. (Currently Amended) A mobile communications device comprising:

memory;

receiver circuitry for receiving messages from network nodes including service interference notification messages indicating service interference at a network node; and
a processor module configured to for:

~~generating~~ generate a list of network nodes identifying network nodes used in routing signals to or from said mobile communications device, ~~and~~ wherein said list comprises ~~includes~~ information identifying each network node which is used by said mobile communications device as at least one of a Mobile IP home agent, a Session Initiation Protocol proxy server and a Session Initiation Protocol location registrar;

~~storing~~ store said list in said memory;

~~processing~~ process, at said mobile communications device, received service interference notification messages to determine if service interference indicated by a received network service interference notification message indicates service interference at a network node used in routing of signals either to said communications device or from said communications device to another network node; [.] and

~~initiating~~ initiate a fault response operation.

43. (Canceled)

44. (Currently Amended) The communications device of claim 42, wherein said processor module is further configured to generate the list to include fault response actions to be taken to respond to faults at network nodes used in routing of IP packets to said mobile node.

45. (Previously Presented) The communications device of claim 44, wherein one of said fault response actions is a Mobile IP registration operation.

46. (Currently Amended) A device including a processor configured to control an end node in a communications system including at least one network node and said end node to implement a method, the method comprising:

generating at the device, from Mobile IP signals directed to said end node or transmitted by said end node, a list of network nodes identifying network nodes used in routing signals to or from said end node, said Mobile IP signals including at least one of a Mobile IP agent solicitation message, a Mobile IP agent advertisement message, a Mobile IP registration message and a Mobile IP registration reply message;

receiving a fault signal indicating a network node fault;

determining, at the device, using said generated list, if the network node fault corresponds to a network node that is used in routing signals to or from said end node; and

if it is determined that the network node fault corresponds to a network node that is used in routing of signals to or from said end node, operating the end node to initiate a fault response operation.

47. (Previously Presented) The device of claim 46, wherein said method further comprises:

comparing network node information included in the received fault signal to information in said generated list identifying at least one network node used in routing signals to or from said end node.

48. (Currently Amended) A computer readable medium embodying machine executable instructions for controlling an end node in a communications system including at least one network node and said end node to implement a method, the method comprising:

generating at the end node, from Mobile IP signals directed to said end node or transmitted by said end node, a list of network nodes identifying network nodes used in routing signals to or from said end node, said Mobile IP signals including at least one of a Mobile IP agent solicitation message, a Mobile IP agent advertisement message, a Mobile IP registration message and a Mobile IP registration reply message;

receiving a fault signal indicating a network node fault;

determining, at the end node, using said generated list, if the network node fault corresponds to a network node that is used in routing signals to or from said end node; and

if it is determined that the network node fault corresponds to a network node that is used in routing of signals to or from said end node, operating the end node to initiate a fault response operation.

49. (Previously Presented) The computer readable medium of claim 48, wherein said method further comprises:

comparing network node information included in the received fault signal to information in said generated list identifying at least one network node used in routing signals to or from said end node.

50. (Currently Amended) A device including a processor configured to control an end node in a communications system including at least one network node and said end node to implement a method, the method comprising:

receiving, at an end node, a fault signal indicating a network node fault ;

determining, at the end node, if the network node fault corresponds to a network node that is used in routing signals to or from said end node; and

if it is determined that the network node fault corresponds to a network node that is used in routing of signals to or from said end node, operating the end node to initiate a fault response operation;

wherein said ~~step of~~ determining if the network node fault corresponds to a network node that is used in routing of signals to or from said end node ~~includes~~ comprises:

comparing network node information included in the received fault signal to stored information identifying at least one network node used in routing signals to or from said end node; and [[,]]

determining said fault response operation as a function of fault response information stored in said end node prior to receiving the fault signal, said stored fault response information relating to a plurality of possible operations; and

wherein said ~~step of~~ determining said fault response operation is also performed as a function of the network node at which the fault occurred with said operation being selected from a plurality of possible operations based on both the type of fault and which one of a plurality of network nodes was the node at which the fault occurred.

51. (Currently Amended) A computer readable medium embodying machine executable instructions for controlling an end node in a communications system including at least one network node and said end node to implement a method, the method comprising:

receiving, at an end node, a fault signal indicating a network node fault;

determining, at the end node, if the network node fault corresponds to a network node that is used in routing signals to or from said end node; and

if it is determined that the network node fault corresponds to a network node that is used in routing of signals to or from said end node, operating the end node to initiate a fault response operation;

wherein said ~~step of~~ determining if the network node fault corresponds to a network node that is used in routing of signals to or from said end node ~~includes~~ comprises:

comparing network node information included in the received fault signal to stored information identifying at least one network node used in routing signals to or from said end node; and [[,]]

determining said fault response operation as a function of fault response information stored in said end node prior to receiving the fault signal, said stored fault response information relating to a plurality of possible operations; ~~and~~

wherein said ~~step of~~ determining said fault response operation is also performed as a function of the network node at which the fault occurred with said operation being selected from a plurality of possible operations based on both the type of fault and which one of a plurality of network nodes was the node at which the fault occurred.

52. (Currently Amended) A mobile communications device, comprising:

memory including a set of stored information indicating network nodes which are used in routing of signals either to said mobile communications device or from said mobile communications device to other network nodes;

receiver circuitry for receiving messages from network nodes including service interference notification messages indicating service interference at a network node;

a list generation module for generating at the mobile communications device, from Mobile IP signals directed to said mobile communications device or transmitted by said mobile communications device, a list of network nodes identifying network nodes used in routing signals to or from said mobile communications device, said Mobile IP signals including at least one of a Mobile IP agent solicitation message, a Mobile IP agent advertisement message, a Mobile IP registration message and a Mobile IP registration reply message; and

a processor for processing, at the mobile communications device, received service interference notification messages to determine, using said generated list, if service interference indicated by a received network service interference notification message indicates service interference at a network node used in routing of signals either to said mobile communications device or from said mobile communications device to another network node, and for initiating a fault response operation.

53. (Currently Amended) The mobile communications device of claim 52, further comprising: wherein said device includes

a wireless transmitter; and

wherein said receiver circuitry comprises ~~includes~~ a radio receiver circuit.